

INNCOM POWER SUPPLIES

Honeywell uses a variety of ancillary equipment such as transformers, power supplies, and interface modules to meet the demands of HVAC, lighting, amenities, and network requirements.



PS563



PS564.DIN

PS563

PS563 40VA NEMA transformer that powers 24V–277VAC circuits in HVAC systems.

PS564.DIN

The PS564.DIN SMPS is a universal input, 12VDC 1A output, and is provided in a DIN rail mountable enclosure with three (3) S5Bus connectors.



PS564 SMPS

PS564 SMPS

The PS564 SMPS is a compact, universal input 12VDC output power supply.



PS565

PS565

The PS565 is a universal input 12VDC, 1A SMPS. This power supply uses a standard 110V outlet and provides two (2) 12VDC outputs.

PS567 MEANWELL DR-30-12

The PS567 is a Meanwell DR-30-12 power supply used for applications which require up to 2A DC output. The PS567 is provided in a DIN rail mountable enclosure.



PS567 Meanwell DR-30-12



PS576

PS576

12 VDC, 4 amp. power supply for the B576.

INNCOM POWER SUPPLIES

PS563 Specifications	
PART NUMBERS	14-2119 - 120-24VAC (40VA) 14-2136 - 24-277VAC (40VA) 14-2020 - 08-24VAC (40VA)
AC VOLTAGE	24-277VAC, 50/60 Hz
CLASS	Isolated class II output
VA RATING	40
MOUNTING	Surface Mounted with two screws
COMPLIANCES	UL

PS564.DIN Specifications	
PART NUMBER	01-9920-2
AC VOLTAGE	100-240VAC, 50/60 Hz
CLASS	Isolated class II output
RATED POWER	12W
MOUNTING	DIN rail mountable
DC VOLTAGE	12VDC, 1A
COMPLIANCES	FCC, UL, CQC, CE Mark, RoHS Approved

PS564 SMPS Specifications	
PART NUMBER	01-9956
AC VOLTAGE	90-277VAC, 50/60 Hz
CLASS	Isolated class II output
RATED POWER	2.4W
MOUNTING	Surface Mounted with two screws
CONNECTORS	Optional three 3-pin Leoco connector for 12VDC

PS565 Specifications	
PART NUMBER	04-4040
AC VOLTAGE	100-120AC, 50/60 Hz
DC VOLTAGE	12VDC, 1A
CLASS	Isolated class II output
RATED POWER	12W

PS567 Meanwell DR-30-12 Specifications	
PART NUMBER	214-311
AC VOLTAGE	90-240VAC, 50/60 Hz
DC VOLTAGE	12VDC, 2A
CLASS	Isolated class II output
RATED POWER	24W
MOUNTING	DIN rail mountable
COMPLIANCES	CB, CE Mark
LED	LED indicator for power on

PS576 Specifications	
PART NUMBER	204-005
AC VOLTAGE	100-240VAC, 50/60 Hz
DC VOLTAGE	12VDC, 4A
CLASS	Isolated class II output
RATED POWER	48W
COMPLIANCES	CB, CE Mark

Honeywell Building Technologies

12 Clintonville Road
Northford, CT 06472
1-800-543-1999
www.inncom.com

01-00152 | 09/20
© 2020 Honeywell International Inc.

Honeywell